

Model FUF126 Ultra-Low Temperature Freezer

Specifications

Application, Rating and Electrical Data

Application	Precision temperature storage for biopharmaceutical and life science research applications
Storage Volume	26cf (736L)
Storage Capacity	528 standard 2" (51mm) boxes
Temperature Range	-50°C to -80°C @ 32°C (90°F) Ambient
Electrical Power	115V 60Hz 220-240V 50/60Hz
Maximum Current	11 FLA
Auto-Voltage Safeguard	Optional boost system
Building Supply Rating	15 amp dedicated ground circuit
Power Plug / Power Cord Length	NEMA 6-15 plug, 7.5ft (2286mm)
Certification / Agency Listing	QPS
Sound Pressure Level (dBA)	<60 dB
Indoor/Outdoor Use	Indoor use only
Application Environment	Non-corrosive, non-flammable, non-explosive, 15°C to 32°C (59°F to 90°F)
Lifetime of Product	10 years

Refrigeration System

Refrigeration System	Two Stage Cascade System
Compressor / Number	Hermetic, variable speed (VCC)
Condenser Type / Number	Air-cooled fin and tube / 1
Expansion Device	TXV valve - high stage Cap tube - low stage
Evaporator Type	Split, cold wall
Defrost Method	Manual
Refrigerant Charge	R-170/R-290 (Low stage) R-290 (High stage)

Energy

Energy Consumption	11.55 kWhr/day
Uniformity	+/-5°C

Warranty

US/Canada	2 years parts, 1 year labor
Outside US/Canada	2 years parts. Consult with your local representative for labor warranty information

*Preliminary specifications. Subject to change.

Controller

Interface	7", full color touchscreen
Power Switch	On/Off with circuit breaker
Controller Type	Microprocessor with touchscreen input and display. Includes USB hub for data retrieval
Security	Lockable door, PIN access control, password setpoints, padlock hasp
Compressor Safeguard	High ambient temperature warning, compressor and condenser over-temperature alarms
Control Sensor	RTD (Platinum) (1 ea)
Communication Port	(1) USB Port (side of door-mounted user interface)
Warm / Cold Alarms	Fully adjustable
Event Log	All alarms, door openings, download via USB
Temperature Log	60 days, download via USB
Access Log	60 days, download via USB
Battery Back-up	20 hour display and alarm battery back-up for touchscreen (12V, lead acid battery)

Dimensions and Construction

Interior (w x h x d) in (mm)	34.4 x 54.1 x 23.3 (874 x 1374 x 592)
Exterior (w x h x d) in (mm)	40.2 x 78.2 x 34.8 (1021 x 1986 x 884)
Exterior (w x h x d) in (mm) (Inc. handle, casters, hinges)	43.8 x 78.2 x 37.5 (1113 x 1986 x 953) Fits through standard 36" (914mm) doorway
Insulation	Premium Vacuum Insulated Panels
Door	1, solid
Access Ports	2, external
Perimeter Heater	Hot gas loop
Compartments & Inner Doors Shelves / Capacity (w x d) In (mm)	5 4 adjustable stainless steel / 160 lb (73 kg) max. cap. 33.9 x 21.9 / (862 x 557)
Casters / Legs	Standard / swivel, locking plus leveling legs
Net Weight	725 lb (328 kg)
Shipping Weight	828 lb (375 kg)
Options / Accessories	LN2 and CO2 back-up systems, -70°C factory preset, voltage boost system
Clearance Requirements	Allow 4" (102mm) behind unit Allow 8" (203mm) above unit

Technical Data Sheet -80°C Ultra-Low Temperature Freezer

